



box ready mastaline

all purpose jointing compound

box ready mastaline is a thinned down premixed all purpose compound that can be applied with automatic tools immediately from the bucket - no mixing required. It can be used interchangeably with standard **mastaline** whenever automatic tools such as a box or taping tool are used.

box ready mastaline can be used with the appropriate automatic tool for 1st, 2nd and 3rd coats, internal and external corners, and screw heads. Refer to the Siniat Plasterboard Installation Guide for jointing and finishing requirements.

performance

Body

Thinned down ready to use through mechanical tools.

Drying

Convenient drying time to obtain thin edges when feathering as it does not dry out too fast.

Colour

Light colour when applied, drying to a white finish.

Sanding

Can be sanded by hand or by electric sanders. Leaves a professional finish.

Safe to Use

Low VOC and non-hazardous (according to Safe Work Australia criteria).

key benefits

- formulated for use with automatic tools
- premixed for easy use and speed
- no additional water required



product information

product size	20 kg in a 15 litre bucket
type	Mid weight air drying premixed all purpose compound
drying time	Allow 24 hours. Drying time will depend on the weather
system usage	✓Bedding ✓Second coat ✓Final coat ✓Fire
voc	<50 g/L
approximate density	1.35 g/cc
approximate volume	14.8 L

application

- **box ready mastaline** is ready to use through mechanical tools. No need to dilute.
- Pump straight from the bucket into the box or automatic taping tool.
- Apply the compound to the wall using appropriate setting method (box, taping tool, corner tool, etc). Ensure sufficient compound under paper tape for maximum adhesion.
- As with all compounds, excessive thinning may cause cracking or increased shrinkage. Do not mix with any other material.
- Ensure adequate ventilation for optimum drying time.
- When using **box ready mastaline** for all three coats, joints must be backblocked, **siniat paper tape** is recommended for use with **box ready mastaline**.
- For a stronger joint, use **siniat paper tape** and **mastabase/longset** or **mastatape universal** for the first two coats, with **box ready mastaline** as the final coat.
- Allow **box ready mastaline** to dry completely between coats. We recommend 24 hours. Drying time will depend on the weather.
- Sand with 180 to 220 grit sand paper.
- **box ready mastaline** will accept most types of decorative finishes. In accordance with AS/NZS 2311 Guide to the painting of buildings, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

optimise product performance by:

- Closing the lid to prevent the compound from drying out.
- Washing tools before product dries and hardens.
- Storing in a dry, well ventilated environment fully protected from the weather.



Quality
ISO 9001



All Siniat products have been developed to meet the specific needs of the Australian market. Products manufactured in Australia comply with quality systems certified as complying with AS/NZS ISO 9001:2008 and meet the requirements of AS/NZS 2588, Gypsum Plasterboard.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **fireshield h**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock** and **trurock hd**. Compliance certificates are available on siniat.com.au.



All Siniat plasterboard and metal products are available on the Siniat Carbon Neutral Opt-In program to help you meet your sustainability goals. Visit siniat.com.au to find out more.

Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit siniat.solutions

Siniat.solutions provides a host of online solutions for your product

siniat SELECT[®]

offers an online system selector and custom design specification proposal, developed by us and catered to your project's requirements.

siniat CALCULATE[®]

is a range of online calculation tools for the professional. Explore siniat.solutions on siniat.com.au.



Etex Australia Pty Ltd

ABN 61 003 621 010
31 Military Road, Matraville
NSW 2036

siniat.com.au



warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit siniat.com.au

technical advice
AU 1300 724 505